



aerotec

Aerotec

\$500.00



Νοαίααδοία εηηρεαεοαογ. Οίρεαεüíεε α³çαεί "íεααíñüεα δαεεγ", íααοííεεε. Áíáδαιάοαεοεαί³ñòü Á++. Óíεíá / óáíεí, ñαííá³ααíñòεεá, àáοíδáñòáδò, áíδèéíδíç³εíá ííεδèòòγ, δαείíáδ 24 á., í³ááεùáíá δáíεíá³ááá-à, á³áδío³εüíá ííεδèòòγ δáíεííáí³íεεá, çíáíøáíεε δ³ááíü øóío, εááεíçéííá íáδááíγ íáíáεü, íδèοíááíεε LED áεñíεáε. Ζί³çàοíδ, δóíεογ "Super Cool 17C", δèδèε δάæèì εííοíδòííáí ñío, δάæèì Óóδáí, δ³εüδòè High Density δà Cold Catal³st, δάæèì ÍÁÉ Favorite Mode. Νò³εεá δíáíòà íà íá³áδ³á áí - 15°C.

ÒÁÓí²xí² ÕÀÐÀÊÕÀÐËÑÕÈÈÈ

Áíóδδ³øíé áεíê

Íáçáà ííááε³: MSMA-12HRDN1-Q ION

Áεáεòδíæεáεáíγ, Á/Ãö/Õ: 220/50/1

Ííòóæí³ñòü, éÁò

Íοíεíáæáíγ: 0,4 - 3.52

Íááδ³á: 0,5 - 3.81

Ííòóæí³ñòü ñííæεááíγ, éÁò

Íοíεíáæáíγ: 0,1 - 1,58

Íááδ³ááíγ: 0,13 - 1,51

Àèòðàòè ïîá³òðÿ, î?/ãîä.: 380 - 600

Ð³ãáíü øóíó, äÁ: 29 - 42

Ãàáàðèèó³ ðíçì³ðè (ØõÃõÃ), ì

Áàç óíàèíâèè: 805x285x205

Ã óíàèíâõ³: 870x360x285

Ãàãà, èã

Ãàãà íàòòí: 8

Çàãàèüíà áàãà: 10

**Çíáí³øíé áéíè**

Òèí èííðãñîðà: Inverter

Éííðãñîð: GMCC ROTARY

Óðáíí

Òèí òðáííó: R410A

Ãàãà òðáííó, èã: 0.8

Áèáèòðíæèáéáííÿ, Ã/Ãõ/Õ: 220/50/1

Àèòðàòè ïîá³òðÿ, î?/ãîä.: 1800

Ð³ãáíü øóíó, äÁ: 56

Ã³áíàòð òðóá, ì

Ãèÿ ð³àèèè: 6.35(1/4")

Ãàçíâà: 9.52(3/8")

Ìàèñ. áíâæèíà ìã³ñòðàè³, ì: 25

Ìàèñ. ïððáíâà àèñîò, ì: 10

Ãàáàðèèó³ ðíçì³ðè (ØõÃõÃ), ì

Áàç óíàèíâèè: 300x555x770

Ã óíàèíâõ³: 900x585x345

Ãàãà, èã

Ãàãà íàòòí: 26

Çàääëüía àääà: 28

Ä³äiäçíí ðíáí÷èõ çíáí³øí³õ òàíiäðàòóð:

Ðåæèì íðíëíäæáíý: (-15) – (+50)°Ñ

Ðåæèì íá³äð³áo: (-15) – (+30)°Ñ

Ãðáíò³ý 2 ðíèè.

[Vendor Information](#)